

Specifications

Trimble MPS865 GNSS Heading Receiver



Receiver Name	MPS865 GNSS Heading Receiver
Configuration Option	
Type	Modular, dual antenna capable
Base and rover interchangeability	Yes
Base operation	Yes, optional
Rover operation	Yes, optional
Heading and Moving Base operation	All models ⁵
Rover position update rate	20Hz upgradeable to 50Hz
Rover maximum range from base	Unlimited
Constellations	GNSS (GPS, QZSS and GLONASS standard). Galileo, BeiDou
Rover operation within a VRS™ network	Yes
Factory options	See Receiver Upgrades below
General	
Keyboard and display	OLED dimmable display. LED status light On/Off key for one-button startup. Audible beeper 4 arrow keys (up, down, left, right) and OK key
Dimensions (L x W x D)	16.5 cm (6.5 in) x 20.6 cm (8.1 in) x 6.5 cm (2.6 in) including
Weight	1.66 kg (3.66 lb) receiver only
Antenna Options	
GA830	Triple Frequency GNSS (GPS, QZSS, Glonass, Galileo, BeiDou), MSS (RTX, OmniSTAR), MSK Beacon
Zephyr™ Model 3 Series	Triple Frequency GNSS (GPS, QZSS, Glonass, Galileo, BeiDou),
Temperature	
Operating	-40 °C to +65 °C (-40 °F to +149 °F) ¹
Storage	-40 °C to +95 °C (-40 °F to +203 °F)
Humidity	Damp Heat 100% humidity, +40 °C (104 °F) IEC 60945:2002
Waterproof	IP67 waterproof and dustproof IEC 60529
Shock and Vibration	
Pole Drop	Designed to survive a 1 m (3.3 ft) pole drop onto a hard surface
Shock	MIL-STD 810F (Fig 516.5-10) (01/2000). Sawtooth (40g/11ms)
Vibration	MIL-STD 810F (Fig 514.5C-17) (01/2000)
Measurements	
	480 GNSS tracking channels (see Receiver Upgrades): GPS L1, L1P(Y), L2P(Y), L2C, L5, L1C GLONASS L1, L1P, L2, L2P, L3, L1/L2 CDMA Galileo E1, E5a, E5b BeiDou B1, B2, B3 QZSS L1, L1 SAIF, L1C, L2C, L5 SBAS L1, L5 DGNSS corrections via MSK Beacon reception Patented method to track encrypted GPS P(Y) Strobe™ Correlator for reduced GNSS multi-path 2-channel SBAS (WAAS/EGNOS/MSAS/GAGAN) GNSS-centric fully independent signal tracking including GPS only, GLONASS only, or BeiDou only
SBAS (WAAS/EGNOS/MSAS) Positioning³	
Horizontal accuracy	± 0.50m (1.6ft)
Vertical accuracy	± 0.85m (2.8 ft)
Code Differential including Beacon Positioning²	
Correction source	DGNSS Base via radio, Internet or MSK Beacon IALA compliant
Horizontal accuracy	±(0.25m + 1 ppm) RMS ±(0.8 ft + 1 ppm)
Vertical accuracy	±(0.50m + 1 ppm) RMS ±(1.6 ft + 1 ppm)
CenterPoint® RTX Positioning⁷	
Accuracy	Horizontal 4cm (0.13 ft) RMS, Vertical 9cm (0.30 ft) RMS
Convergence time for specified precisions	5 minutes in select regions, and typically 30 minutes worldwide
RTK Positioning²	
Horizontal accuracy	8 mm + 1 ppm RMS (0.026 ft + 1 ppm RMS)
Vertical accuracy	15 mm + 1 ppm RMS (0.05 ft + 1 ppm RMS)
Trimble VRS⁸	

Specifications

Trimble MPS865 GNSS Heading Receiver

Horizontal accuracy	8 mm + 0.5 ppm RMS (0.026 ft +0.5 ppm)
Vertical accuracy	15 mm + 0.5 ppm RMS (0.05 ft +0.5 ppm)
Precise Heading²	
Heading accuracy 2m baseline	0.09° RMS
Heading accuracy 10m baseline	0.03° RMS
Pitch or Roll	Typically twice the baseline accuracy
Post-processing accuracy	
Static	3 mm + 0.5 ppm HRMS / 5 mm + 0.5 ppm VRMS
High precision static	3 mm + 0.1 ppm HRMS / 3.5 mm + 0.4 ppm VRMS
Power	
Internal	Removable internal battery 7.4V 3.7 Ah Li-Ion battery Integrated charging circuitry - Battery will charge from external power source
External	9-36 V DC external power input (EN2282, ISO7637-2). Over-voltage protection Receiver automatically turns on when connected to external power
Power consumption	5.9 W in rover mode with internal receive radio 12.9 W in base station mode with internal transmit radio
Operation Time on Internal Battery	
Rover	6 hours
Base station with UHF transmitting	4 hours
Regulatory Approvals	
	FCC: 47 Part 15 CE Mark (R&TTE Directive): EN 301 489-1/-5/-17/-24, EN 300 440-1/-2, EN 300 328, EN 300 113-2, EN 60950-1, EN 50371 61000-3-2/-3, EN 55032, EN 550024, EN 301 908-1, ISO7637-2 Canadian ICES-003. Cet appareil numérique de la classe B est RoHS - 2 compliant WEEE compliant Galvanic Insulation 500V (Except USB)
Communications	
Lemo (Serial 1) - Port A	RS232, external power input. Use for UHF radio configuration
Serial 2 - Port B	9 pin Male. RS232. Switchable to RS422
Serial 3 - Port F	9 pin Male. RS232, 1PPS, NMEA2000 (CAN)
1PPS (1 pulse-per-second)	Available on Port F. User settings for period, offset, active edge
USB	1 mini USB OTG
Ethernet	RJ45 connector. DHCP Server, Static IP, Server mode
WiFi	802.11 b/g/n. SMA connector for WiFi/Bluetooth external antenna
Bluetooth wireless technology	Bluetooth v4.0+EDR/LE, Bluetooth v2.1+EDR SMA connector for WiFi/Bluetooth external antenna
Cellular	3.5G quad band GSM (850/1800/1900 MHz) / penta-band UMTS module (800/850/900/1900/2100 MHz). SMA connector for
Network Protocols	
HTTP (web browser GUI)	Yes, via Wi-Fi, Ethernet, or cellular
NTP Server	Yes
TCP/IP or UDP	Yes
NTRIP	NTRIP v1 and v2, Client mode. FTP server. Caster is optional
RTK Networks	VRS, FKP, MAC
mDNS/uPnP Service discovery	Yes
Dynamic DNS	Yes
eMail alerts	Yes
Network link to Google Earth	Yes
Supported data formats	
Correction Inputs	CMR™, CMR+™, CMRx, RTCM 2.x, RTCM 3, ATOM
Correction Outputs	CMR™, CMR+™, RTCM 2.x, RTCM 3, ATOM
Data Outputs	NMEA0183, NMEA2000, 1PPS Time Tags, ATOM
External GSM/GPRS, cell phone support	Supported for Trimble IBSS and VRS services
Integrated radios (optional)	Internal MSK Beacon ⁶ and 450 MHz (UHF) or Internal MSK Beacon Beacon only 12.5 kHz or 25 kHz spacing available -114 dBm (12 dB SINAD)
Channel spacing (450 MHz)	Frequency range 283.5–325.0 kHz Channel spacing 500 Hz
Sensitivity (450 MHz)	MSK bit rate 50, 100, and 200 bps
Internal MSK Beacon receiver	

Specifications

Trimble MPS865 GNSS Heading Receiver

Receiver Upgrades

Constellation
Frequency
Precision
Function

Demodulation minimum shift key (MSK)

Galileo, BeiDou
Triple Frequency
Precision 7/2 Rover, Precise GNSS
Precise Base, Precise Rover, Data logging, 50 Hz, Data logging,
NTRIP Caster

Data Logging

Memory limit

6.6 Gb internal memory (option). Expandable through external
USB sticks

Notes

- 1 Receiver will operate normally to -40°C .
- 2 Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, interference and atmospheric conditions. Always follow recommended practices.
- 3 Depends on SBAS system performance.
- 4 Bluetooth type approvals are country specific. For more information, contact your local Trimble office or representative.
- 5 Two antennas (See Antenna Options) must be connected for heading.
- 6 One of the antennas must be a MSK Beacon capable one such as GA830 for beacon signal reception.
- 7 Available late 2018. Marine use is controlled - Contact Trimble Marine for details. Receiver accuracy and convergence time varies based on GNSS constellation health, level of multipath, and
- 8 Networked RTK PPM values are referenced to the closest physical base station

Specifications subject to change without notice.

© 2018, Trimble Inc. All rights reserved. Trimble, the Globe & Triangle logo are trademarks of Trimble Inc, registered in the United States and in other countries. CMR, CMR+, CMRx, VRS, CenterPoint RTX and Zephyr are trademarks of Trimble Inc. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Inc. is under license. All other trademarks are the property of their respective owners.

Trimble Civil Engineering and Construction Division

10368 Westmoor Drive
Westminster, Colorado 80021
USA
800-361-1249 (Toll Free)
+1-937-245-5154 Phone
+1-937-233-9441 Fax
www.trimble.com

Trimble Authorized Distribution Partner